



NEO Monitors LaserGas™ is using Tunable Diode Laser Absorption Spectroscopy (TDLAS) i.e a non-contact optical measurement method employing solid-state laser sources. The sensor remains unaffected by contaminants corrosives and does not require regular maintenance. The absence of extractive conditioning systems further improves availability of the measurements and eliminates errors related to sample handling. The monitor is mounted directly onto flanges, which include purge gas connections and a tilting mechanism for easy alignment. Continuous purge flow prevents dust and other contamination from settling on the optical windows. Once power and data lines are connected, measurements are performed in real-time.

Features	Applications	Customer benefits
<ul style="list-style-type: none"> • Response time down to 1 second • No gas sampling: In-situ measurement • Non contact measurement • No interference from background gases • Applicable for many process conditions: <ul style="list-style-type: none"> - high/low temperature - high dust - corrosive gases • Line measurement, integral concentration over the full stack diameter • ATEX and CSA certified • TÜV, MCERTS, GOST approved technology • Integrated span check option available • Suitable for harsh environment • No zero drift • Stable calibration • Long Path lengths 	<p>LaserGas™ II SP is designed for reliable and fast measurement of all kinds of gases in any environment, most typically:</p> <ul style="list-style-type: none"> • Chemical industry • Petrochemical industry • Metal industry • Power plants • Waste incinerators • Cement industry • Automotive industry • Scrubber technology • Glass industry • PVC production • Pulp and paper • and more 	<ul style="list-style-type: none"> • In-situ monitoring • Highly reliable real time analyzer • Low maintenance cost • Reduce emission to the environment • Easy to install and operate • Reduce daily operation costs • Optimize process • Well proven measurement technique

LaserGas™ II SP

Technical Data

Specifications Optical path length: Typically 0.5-20m Response time: 1 – 2 sec Accuracy: Application dependent Repeatability: 1% of range (gas & application specific) Environmental conditions Operating temperature: -20 °C to +55 °C (special version up to +65 °C on request) Storage temperature: -20 °C to +55 °C Protection classification: IP66 Inputs / Outputs Analog output (1-3): 4 - 20 mA current loop (concentration, transmission) Digital output(Optional): TCP/IP, MODBUS, fibre optic Relay output (3): High gas, Maintenance Warning and Fault Analog input (2): 4 – 20 mA process temperature and pressure reading Input power supply unit: 100 – 240 VAC, 50/60 Hz, 0.36 – 0.26 A Output power supply unit: 24 VDC, 900 – 1000 mA	Ratings Input transmitter unit: 18 – 36 VDC, max. 20W 4 – 20 mA output: 500 Ohm max. isolated Relay output: 1 A at 30 V DC/AC Safety Laser class: Class 1 according to IEC 60825-1 CE: Certified. EMC: Conformant with directive 2014/30/EU Approvals IECEX/ATEX zone 1: II 2 G Ex px IIC T5 Gb II 2 D Ex p IIIC T64°C Db IECEX/ATEX zone 2: II 3 G Ex nA nC op is IIC T4 Gb II 3 D Ex td A22 T100°C CSA: Class I, Div. 2, Groups A, B, C and D; Temp. Code T4; non-incendive Installation and Operation Flange dimension alignment: DN50/PN10 or ANSI 2"/150lbs (other dimensions on request) Alignment tolerances: Flanges parallel within 1.5°	Purge flow: Dry and oil-free pressurised air or nitrogen 10 - 50 l/min (application dependent) Maintenance Calibration: Check recommended every 12 months Validation: In-situ span check with optional internal cell (application dependent) Dimension and weight Transmitter unit: 405 mm x 270 mm x 170 mm 6.2 kg Transmitter unit: 405 mm x 270 mm x 310 mm (Ex version) 7.9 kg Receiver unit: 355 mm x 125 mm x 125 mm 3.9 kg Power supply unit: 180 mm x 85 mm x 70 mm 1.6 kg
---	---	---

Gas	Detection limit (ppm)	Max temp (°C)	Max pressure (BarA)
NH ₃	0,15	600	2
HCl	0,05	600	2
HF	0,015	400	2
H ₂ S	3	300	2
O ₂	100	1500	20
% H ₂ O	50	1500	2*
ppm H ₂ O	0,1	1000	2
% CO	30	1500	2*
% CO ₂	100	1500	2*
ppm CO	0,3	1500	2
ppm CO ₂	1	300	2
NO	10	350	2
N ₂ O	1	200	2
ppm CH ₄	0,2	300	3
% CH ₄	100	1000	3
NO ₂	5	200	1,5
HCN	0,3	300	2

NOTE: Detection limits are specified as the 95% confidence interval for 1m optical path and gas temperature / pressure = 25 °C / 1 BarA. Measured in N₂.

Other gases available on request.

Dual Gas: NH₃+H₂O, HCl+H₂O, CO+CO₂, CO+H₂O, CO+CH₄, O₂+temp, CO+temp.

*Higher pressure available on request for certain gases.

Please contact us for details.

TÜV and MCERTS, GOST approval available for some gases.

Your local distributor:

*NEO Monitors reserve the right to change specifications without prior notice



NEO Monitors AS • Part of the Nederman Group • Prost Stabells vei 22 • N-2019 Skedsmokorset, Norway
Phone +47 67 97 47 00 • www.neomonitors.com